



Language
Technologies
Institute

Carnegie
Mellon
University

Multimodal Machine Learning

Lecture 9.2: Reasoning – Inference Time

Louis-Philippe Morency

** Original course co-developed with Tadas Baltrusaitis.
Major revision co-developed with Paul Liang. Co-lecturers
included Yonatan Bisk, Daniel Fried and Carlos Busso.*

Administrative Stuff

Upcoming Course Assignments

Midterm project report (due this Sunday 10/25 at 8pm ET)

- For each N-1 research idea, implement a first (baseline) model
 - The emphasis is on the result discussion (to update research ideas)
- Read carefully the instructions!!

Midterm project presentations (next week)

- In-class presentations: Tuesday 10/27 and Thursday 10/29
 - One presentation per team, maximum of N+1 minutes
 - Focus on the updated research ideas (from report)
- Attendance required for both sessions
 - Give feedback to at least 6 teams per session
- Upload your slides on shared Google Drive
 - Same laptop used for all presentations

Attendance using Poll Everywhere



- 1 Scan QR Code
or
<https://pe.app/mmm1>
- 2 Enter your AndrewID
(as your “name tag”)
- ✗

Do not try to sign-in
- 3 Click “Share location”



Language
Technologies
Institute

Carnegie
Mellon
University

Multimodal Machine Learning

Lecture 9.2: Reasoning – Inference Time

Louis-Philippe Morency


** Original course co-developed with Tadas Baltrusaitis.
Major revision co-developed with Paul Liang. Co-lecturers
included Yonatan Bisk, Daniel Fried and Carlos Busso.*

Objectives of today's class

- Inference Design
 - Logical inference, causal inference
- Reasoning Traces
 - Chain-of-thought prompting and few-shot learning
 - Test-time compute scaling, and its multimodal ceiling
- Two strategies for improving multimodal reasoning
 - Improving perception
 - RLVR, GRPO, rule-based rewards
 - Active perception
 - Visual search, frame selection, designed vs learned policies

Reasoning

Definition: Combining knowledge, usually through multiple inferential steps, exploiting multimodal alignment and problem structure




Reasoning


Definition: Combining knowledge, usually through multiple inferential steps, exploiting multimodal alignment and problem structure

Sub-challenges:

Structure Modeling





Intermediate concepts



External Knowledge



Inference Paradigm



Inference Design

Logical Inference


Inference through logical operators in question



*Is there beer AND is there a
WINE GLASS?*



*Is the man NOT wearing
shoes AND is there beer?*



Is there beer?

Is the man wearing shoes?

Adversarial antonyms



Logical connectives



Basic premises




Existing models struggle to capture logical connectives.
How can we make them more logical?

Logical Inference

Inference through logical operators in question



*Are they in a restaurant **AND** are they all boys?*



*Differentiable **AND** composition operator!*

*Also applies to other logic connectives:
AND, OR, NOT*



Are they in a restaurant?



Are they all boys?

Causal Inference

Causal VQA: does my multimodal model capture causation or correlation?

Covariant VQA

Target object in question

Q: How many zebras are there in the picture?


A: 2



Baselines:

2

i.e., treatment
variable



BUT: correlation or causation?

[Agarwal et al., Towards Causal VQA: Revealing & Reducing Spurious Correlations by Invariant & Covariant Semantic Editing. CVPR 2020]

Causal Inference

Causal VQA: does my multimodal model capture causation or correlation?

Covariant VQA

Target object in question

Q: How many zebras are there in the picture?

A: 2

zebra removed A: 1




Baselines:

2

2

i.e., treatment
variable



Interventional conditional: $p(y|do(zebras = 1))$

Existing models struggle to adapt to targeted causal interventions.
How can we make them more robust to spurious correlations?

Causal Inference

Causal VQA: does my multimodal model capture causation or correlation?

Invariant VQA


Target irrelevant object

Q: What color is the balloon?

A: red



Baselines: **pink**



Is my model picking up irrelevant objects?

[Agarwal et al., Towards Causal VQA: Revealing & Reducing Spurious Correlations by Invariant & Covariant Semantic Editing. CVPR 2020]

Causal Inference

Causal VQA: does my multimodal model capture causation or correlation?

Invariant VQA

Target irrelevant object

Q: What color is the balloon?

A: red


umbrellas removed; A: red



Baselines:

pink

red





Interventional conditional: $p(y|do(no\ umbrella))$

Existing models struggle to adapt to targeted causal interventions.
How can we make them more robust to spurious correlations?

Causal Inference

Causal inference via data augmentation



[Agarwal et al., Towards Causal VQA: Revealing & Reducing Spurious Correlations by Invariant & Covariant Semantic Editing. CVPR 2020]

Reasoning Traces

Chain-of-Thought and Reasoning Traces

Q: A juggler can juggle 16 balls. Half of the balls are golf balls, and half of the golf balls are blue. How many blue golf balls are there?


A: *Let's think step by step.*

(Output) There are 16 balls in total. Half of the balls are golf balls. That means that there are 8 golf balls. Half of the golf balls are blue. That means that there are 4 blue golf balls. ✓

`<think>` There is ... `</think>`


`<answer>` The answer is ... `</answer>`

MLLM Reasoning Traces




<think>
First, find the bus.
Now look at the passengers inside it.
Is it full?
</think>
<answer> Yes **</answer>**

Computation layout



MLLM Reasoning Traces and Few-Shot Learning



<think>

First, what is the person doing?
They are being pulled behind a boat on water.

-> 3a decomposition

The board is short and wide, with bindings for both feet.

-> 3b intermediate concepts (in text)

Boards used behind boats with foot bindings are wakeboards.



-> 3c knowledge, recalled not retrieved

</think>

<answer> A wakeboard **</answer>**

Traces are flexible, but nothing guarantees they're right

Multiple CoT Reasoning Traces (Test-time Scaling)




Observation 1: Vision encoder runs once, deterministically.


Observation 2: Generator-verifier gap can be small (hard to verify)

EMMA: Can MLLMs Reason in Multimodality?

Multimodal reasoning question in EMMA




Question: Three point charges, of charge $+Q$, $-2Q$, and $+3Q$, are placed equidistant as shown. Which vector best describes the net direction of the electric force acting on the $+Q$ charge?



Human reasoning

The direction of the electric force due to $-2Q$ and $+3Q$ can be visualized with a quick free-body sketch of the electric forces:



Model reasoning (GPT-4o)

1. Forces Due to the Charges:

- The $-2Q$ charge attracts the $+Q$ charge. (Force points downward-left).
- The $+3Q$ charge repels the $+Q$ charge. (Force points downward-right). ❌

2. Force Magnitudes (Coulomb's Law):

- Force due to $-2Q$: $F_{-2Q} = \frac{2kQ^2}{r^2}$.
- Force due to $+3Q$: $F_{+3Q} = \frac{3kQ^2}{r^2}$.

Error: While the model understands that like charges repel, it incorrectly identifies the force from $+3Q$ to $+Q$ as downward-right ↘, when it should be upward-left ↖.


EMMA: Can MLLMs Reason in Multimodality?

Model	Method	N=1	N=2	N=4	N=8	N=16
GPT-4o	Majority Voting		—	37.25	36.25	38.25
	BoN (self)		35.50	35.75	36.75	—
	BoN	36.00	<u>40.75</u>	36.25	36.5	—
	Tournament		<u>40.75</u>	39.25	41.25	35.25
	Pass@N		45.00	53.25	65.75	74.00
Gemini 2.0 Flash	Majority Voting		—	37.75	39.25	39.75
	BoN (self)		38.25	36.50	36.00	—
	BoN	36.25	36.75	37.00	<u>40.25</u>	—
	Tournament		36.75	37.25	40.75	38.75
	Pass@N		45.25	56.25	64.50	75.00

Observation 1: majority voting is *mostly flat*. Most samples inherit the same misperception and converge on the same wrong answer.

Observation 2: The gap between Pass@N and the other rows is the verifier gap. The correct answer is in the set of traces, but not selected.

EMMA: Can MLLMs Reason in Multimodality?



Over 80% of errors are visual or perceptual; under 10% are textual reasoning.

Two Strategies to Improve Multimodal Reasoning




Improving Visual perception




Active Perception

Improving Visual Perception in Multimodal Reasoning

Improving Visual Perception



Challenge: If we reward the answer, then maybe only the LM decoder ends up learning...




Rule-based reward functions

Solution: Images are grounded in the real world...

... so visual questions often have a concrete ground truth




RL Vocabulary with MLLM




RL term	In an MLLM	Example: counting
Policy π_{θ}	the MLLM itself	Model answering
Action a_t	next token	“8”
State s_t	prompt + image + tokens so far	
Trajectory	the full response	reasoning + answer (“8”)
Reward r	score at the end	digit match $\rightarrow$ 0/1

GRPO with Multimodal LLM



NOTE: if all trajectories get the same reward, then $\text{std} \rightarrow 0$, no gradient

RL with Verifiable Rewards (RLVR)




Verifiable (rule-based) rewards

Domain	Verifier
Counting	Digit match
OCR	Edit distance
Grounding	Box overlap
Detection	Match boxes, then overlap



In contrast to RLVR...

RLHF: Learns a reward model based on preference annotations. Needed when nothing can verify the answer

Perception-R1: GRPO + RLVR for MLLM



Perception-R1: Matching Prediction Boxes



Perception-R1: A Surprising Result...

case	Visual Grounding			OCR	Visual Counting		Detection
	RefCOCO	RefCOCO+	RefCOCOg	PageOCR	Pixmo _{val}	Pixmo _{test}	COCO2017
Perception-R1	89.1	81.7	85.7	98.4	78.1	75.6	31.9
w/o reward matching	-	-	-	-	77.1	75.4	23.5
w/o RL	86.8	77.1	83.3	94.4	60.2	50.5	16.1
w thinking	75.1	67.9	71.3	77.3	74.9	72.8	25.7
w/o thinking	89.1	81.7	85.7	95.7	78.1	75.6	28.1

Surprising result: Explicit thinking processes prove non-essential for contemporary visual perception.

Active Perception

Active Perception

"They Did Not Expect Him", painting by Ilya Repin, 1884



Where to look?

What to look at first?

What to remember?


Also important in robotics...

Active observer: one “engaged in some kind of activity whose purpose is to control the geometric parameters of the sensory apparatus.”

— Aloimonos, Weiss & Bandyopadhyay, *Active Vision*, IJCV 1988

Yarbus, *Eye Movements and Vision*, Plenum Press, 1967

Active Perception with MLLMs



Challenge: MLLM's visual evidence comes from a one-shot, query-independent encoder

Solution: Allow the MLLMs to be active in its perception of the world (active agent)

Goal	Action	Domain
Where	crop, zoom	Spatial (e.g., visual search)
When	frame selection	Temporal (e.g., long videos)
What if	generate alternative hypotheses	Epistemic (e.g., causal inference)

Guided Visual Search

Where to look?

What to look at first?

What to remember?



*"They Did Not Expect Him",
painting by Ilya Repin, 1884*

V* Bench dataset

Tell me the number of that player who is shooting.



GPT-4V:
The player who is shooting
is wearing the number "10."

SEAL:
The number of that player
who is shooting is **eight**.


Which company does that little doll belong to?



GPT-4V:
The little doll belongs to the
company "**Rubbermaid
Commercial**".

SEAL:
The little doll belongs to
Intel.


V* Visual Search Algorithm



The search prior is semantic, not visual.

Zoomed on the people in the image

Results Stored in Visual Working Memory



Where? the spatial domain


Active Perception: the model chooses where in the image to spend its resolution.

Designed Policy

While the components are learned, the policy is not.

*Researchers designed the rules (e.g., confidence threshold) about **when** to search again.*


VideoAgent: Frame selection for Video Reasoning



Wang et al., VideoAgent: Long-form Video Understanding with Large Language Model as Agent, 2024

Act2See: Retrieval + Generation


Round 1 Instruction: Provide a step-by-step ... (full prompt in Table 1). Question: What is directly to the left of the black phone booth at the station where the train stops in the evening?
Choices: 0) ...



Gemini 2.5 Pro

Round 1 Output: ... *<think>*...First, I need to find the scene where the train stops at a station in the evening.... *<retrieve>* train stopped at station platform in the evening with black phone booth *</retrieve>* ... (the rest after *</retrieve>* are discarded)

Act2See: Retrieval + Generation




Round 2 Instruction: ... You will be given your half-completed response from last round... (full prompt in Appendix). Question: ... Choices: ... Your half-completed response: Let me answer this question... <retrieve> train stopped at station platform in the evening with black phone booth </retrieve> <frame>



Gemini 2.5 Pro

Round 2 Output: now I see the train station in the evening with the black phone booth, to the immediate left </think> <answer> A display of flowers. </answer>

From Designed to Learned Policy



Same RL, new environment...

Something outside the model executes the action and writes into the context

RL term	In an MLLM	with Actions
Policy π_{θ}	the MLLM itself	<i>unchanged</i>
Action a_t	next token	<i>unchanged</i> – “crop(...)” is just tokens
State s_t	prompt + image + tokens so far	+ observations inserted by the environment
Trajectory	the full response	multi-turn: generate → observe → generate
Reward r	score at the end	<i>unchanged</i>


Interleaved Multi-modal Chain-of-Thought



[Begin of iMCoT] The image shows a living room ... To the right side of the image, there is a laptop on a black surface ... There is no visible clock near the laptop or any part of the room that looks like a clock. Therefore, we cannot confirm the presence of a clock to the left of the laptop.

Since the image alone does not provide sufficient information to answer the question definitively, we need to identify the potential area where the clock might be, if it exists ... I will generate the ROI for this area.

`{"bbox_2d": [2, 189, 171, 298], "label": "area potentially containing the clock"}`



The zoomed-in image shows part of a TV stand with a CRT television ... there is no visible clock in the provided zoomed-in region, and the user's question still cannot be answered definitively based on this image.

Given this, let's re-evaluate the area to see if we can detect any other potential clock candidates. We may need to adjust or re-examine the area.

`{"bbox_2d": [145, 18, 226, 220], "label": "region of the bookshelf"}`




The zoomed-in image now shows a bookshelf next to a TV. On the shelf, there is a round object that appears to have the shape and design of a clock, which makes it a likely candidate being referenced in the original question.


Since we have identified the clock's location in the current zoom-in, this satisfies the condition. **[End of iMCoT]**

<answer> Yes, the clock is to the left of the laptop. </answer>

Interleaved Multi-modal Chain-of-Thought



Curiosity-Driven RL



The Learning Trap



Standard RL: the policy learns to **bypass** visual actions in reasoning.

Two Solutions:



Warm-Start Instruction Tuning lays the **foundation** for effectively using visual operations.



Curiosity-Driven RL encourages the **exploration and practice** of visual actions in reasoning

Wang et al., Pixel Reasoner: Incentivizing Pixel-Space Reasoning with Curiosity-Driven Reinforcement Learning, 2025